REV. NO./REPL. SDS GENERATED 2

Honeywell

Prestone Products Corporation

39, Old Ridgebury Road

Danbury

USA

06810-5109



# SAFETY DATA SHEET Prestone antifreeze / coolant RTU

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME

Prestone antifreeze / coolant RTU

PRODUCT NO.

PRES01R

SUPPLIER

Amtrapola

41-200 Sosnowec

**UL Schonowz** 

Bedzin

Poland

+48 832 294 4100

+48 832 294 4139

m.sieradzki@amtra.com.pl A Honeywell Consumer Products

**Group Company** 

**EMERGENCY TELEPHONE** 

FR - INRS Tél :+33 (0)1.45.42.59.59 24hrs B - Antigifcentrum Tél: +32.70.245.245 24hrs NL -

Rijksinstituut voor Volksgezondheid en Milieuhygiëne: tel. +31 (0)30 274 91 11 24hrs D - +49 (0)89

MANUFACTURER

19240 UK - 00 44 (0) 161 491 73910ffice hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167

# **2 HAZARDS IDENTIFICATION**

Harmful if swallowed.

CLASSIFICATION (1999/45)

Xn;R22.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name :::	EC No.	CAS-No.	Content %	Classification (67/548/EEC)			
ETHANEDIOL	203-473-3	107-21-1	30-60%	Xn;R22			
2-ETHYLHEXANOIC ACID	205-743-6	149-57-5	1-5%	Repr. Cat. 3;R63			

The Full Text for all R-Phrases is Displayed in Section 16

## **4 FIRST-AID MEASURES**

## INHALATION

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air. SKIN CONTACT

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing. **EYE CONTACT** 

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

## Prestone antifreeze / coolant RTU

# **5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA** 

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

## **6 ACCIDENTAL RELEASE MEASURES**

SPILL CLEAN UP METHODS

Collect in containers and seal securely. Runoff or release to sewer, waterway or ground is forbidden.

## **7 HANDLING AND STORAGE**

**USAGE PRECAUTIONS** 

Avoid spilling, skin and eye contact. Do not handle broken packages without protective equipment.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Keep separate from food, feedstuffs, fertilisers and other sensitive material. Store above freezing.

#### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name		STD TWA - 8 Hrs		STEL - 15 Min		Notes	
ETHANEDIOL		 WEL		10 mg/m3(Sk)		104	
	•					mg/m3(Sk)	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT





# **ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

# Prestone antifreeze / coolant RTU

**APPEARANCE** 

Liquid

## 10 STABILITY AND REACTIVITY

**STABILITY** 

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with acids and oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

## 11 TOXICOLOGICAL INFORMATION

INHALATION

No specific health warnings noted.

**INGESTION** 

Harmful if swallowed.

SKIN CONTACT

May cause sensitisation by skin contact. Liquid may irritate skin.

**EYE CONTACT** 

May cause severe irritation to eyes.

#### 12 ECOLOGICAL INFORMATION

# 13 DISPOSAL CONSIDERATIONS

**DISPOSAL METHODS** 

Dispose of waste and residues in accordance with local authority requirements.

# 14 TRANSPORT INFORMATION

**GENERAL** 

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA,

ADR/RID).

No transport warning sign required.

ENVIRONMENTALLY HAZARDOUS

SUBSTANCE/MARINE

POLLUTANT

No.

## 15 REGULATORY INFORMATION

**LABELLING** 



Harmful

CONTAINS

**ETHANEDIOL** 

RISK PHRASES

R22

Harmful if swallowed.

**REVISION DATE 13/02/2007** 

REV. NO./REPL. SDS GENERATED 2

# Prestone antifreeze / coolant RTU

# SAFETY PHRASES

S2	Keep out of the reach of children.
S13	Keep away from food, drink and animal feeding stuffs.
S46	If swallowed, seek medical advice immediately and show this container or label.
S56	Dispose of this material and its container to hazardous or special waste collection point.

# **EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Detergents Regulation EC 648/2004 NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

# **16 OTHER INFORMATION**

REVISION DATE

13/02/2007

REV. NO./REPL. SDS GENERATED 2

RISK PHRASES IN FULL

R22

Harmful if swallowed.

R63

Possible risk of harm to the unborn child.